BINDURA UNIVERSITY OF SCIENCE EDUCATION

FACULTY OF SCIENCE

DEPARTMENT OF COMPUTER SCIENCE



Development of an AI and IoT-Based Smart Water Quality Monitoring System for Community Water Sources in Zimbabwe: A Case Study of Bindura

BY

PRAISE NGOSHI

B191330A

SUPERVISOR: P. CHAKA

JUNE 2026

Approval Form

The undersigned certify that they have supervised the student **PRAISE NGOSHI** dissertation entitled **Development of an AI and IoT-Based Smart Water Quality Monitoring System for Community Water Sources in Zimbabwe: A Case Study of Bindura** submitted in partial fulfilment of the requirements for the Bachelor of Computer Science at Bindura University of Science Education.



---------- 30/05/2026

STUDENT ----------DATE



---------- 30/05/2026

SUPERVISORS ----------DATE



---------- 30/05/2026

CHAIRPERSON ----------DATE

EXTERNAL EXAMINER ----------DATE

DEDICATION

This dissertation is dedicated to my father and mother for their unwavering support, encouragement, and sacrifices throughout my academic journey. Their belief in my abilities gave me the strength and determination to persevere through every challenge.

I also dedicate this work to my lecturer whose guidance, knowledge, and inspiration contributed significantly to my growth as a student and researcher.

ACKNOWLEDGEMENT

First and foremost, I would like to thank God Almighty for His grace, strength and guidance throughout this journey. Without Him completing this dissertation would not have been possible.

I am deeply grateful to my supervisor, Mr P. Chaka, for his patience, constructive feedback, and unwavering support from the proposal stage of this work to its completion. His insights shaped both the direction and quality of this dissertation.

I also acknowledge the Department of Computer Science, Bindura University of Science Education, for providing the academic environment and resources that made this work possible.

To my family, thank you for your encouragement, prayers, and sacrifices .To my friends and colleagues, thank you for the moral support.

Any errors or omissions in this work, remain entirely my own.

ABSTRACT

Access to safe water remains a severe challenge in Zimbabwean communities due to limitations of traditional water quality monitoring methods which are manual, labor-intensive, and lack real-time capabilities. This delay in contamination detection increases public health risks from water-borne diseases. This study designed and evaluated an AI and IoT-based smart water quality monitoring and early warning system to address these challenges, using selected boreholes and wells in Bindura as a case study.ESP32 microcontroller simulation modules with IoT sensor models to measure pH, turbidity, temperature, dissolved oxygen, and total dissolved solids. Data is transmitted via simulated Wi-Fi/GSM channels to a cloud-based MySQL database , where Python-based AI models perform predictive trend analysis and anomaly detection. A web dashboard provides simulated real-time visualization and simulated SMS/email alerts to water authorities when unsafe conditions are detected. Following a Design Science Research methodology, the prototype was evaluated across four simulated monitoring sites in Bindura and evaluated for accuracy, reliability, and usability. Results showed sensor accuracies of 94.2% to 98.9% compared to reference benchmark datasets. The AI model achieved an ROC-AUC of 0.96 and F1-score of 0.90, detecting 89% of genuine contamination events with an average alert time of 4.3 minutes. Usability evaluation with five water authorities yielded mean ratings above 4/5 for clarity and usefulness.The findings demonstrate that integrating IoT and AI provides a reliable, accurate, and usable solution for continuous water quality surveillance in resource-constrained environments. The simulated system offers water authorities a practical tool for proactive contamination management and is recommended for broader deployment.

Keywords: Artificial Intelligence (AI), Internet of Things (IoT), Water Quality Monitoring, Smart Water Management, Early Warning System, Predictive Analytics, Anomaly Detection, Simulation-Based Monitoring, Environmental Monitoring, Bindura.

LIST OF FIGURES

Figure 3. 1: data sources analysis 26
Figure 3. 2: dataset overview 27
Figure 3. 3:System Overview Analytics 29
Figure 3. 4: System Prediction 29
Figure 3. 5:Readings Latest Predictions 30
Figure 3. 6: Prediction result 31
Figure 3. 7: Latest sources 32
Figure 3. 8: Water Sources Management 32

LIST OF TABLES

Table 4. 1:Sensor Accuracy Validation Results 36
Table 4. 2: Communication Performance by Location 37
Table 4. 3: Time-Series Forecasting Results 39
Table 4. 4: Anomaly Detection Model Performance 40
Table 4. 5: System Usability Evaluation Results .....**Error! Bookmark not defined.**

Table of Contents

CHAPTER 1: INTRODUCTION 1
1.0 Introduction 1
1.1 Background to the Study 2
1.2 Problem Statement 3
1.3 Aim of the Study 4
1.4 Research Objectives 4
1.5 Research Questions 4
CHAPTER 2: LITERATURE REVIEW 7
2.1 Introduction 7
2.2 Conceptual Framework 7
2.2.1 Data Collection through IoT Sensors 8
2.2.2 Data Transmission and Connectivity 8
2.2.3 Data Processing Using Artificial Intelligence 9
2.2.4 Decision Support and Visualization Systems 9
2.2.5 Relationship Between System Inputs, Processes and Outputs 10
2.3 Theoretical Framework 11
2.3.1 Internet of Things Architecture Theory 11
2.3.2 Machine Learning Predictive Analytics Theory 12
2.3.3 Integration of IoT Architecture and Machine Learning Theory 13
2.4 Empirical Evidence 14
2.4.1 IoT-Based Water Quality Monitoring Systems 14
2.4.2 IoT Technologies for Environmental Monitoring 15
2.4.3 Artificial Intelligence for Water Quality Prediction 15
2.4.4 Adoption of IoT Technologies in Developing Countries 16
2.4.5 Smart Water Management in Africa 16
2.5 Research Gap Analysis 17
2.5.1 Limited Research in Developing Countries 17

2.5.2 Limited Integration of Artificial Intelligence in Monitoring Systems 18
2.5.3 Limited Focus on Community Water Management Systems 18
2.5.4 Need for Integrated Smart Monitoring Systems 19
2.5.5 Contribution of the Current Study 19
2.6 Chapter Summary 19
CHAPTER 3: RESEARCH METHODOLOGY 21
3.0 Introduction 21
3.1 Research Philosophy 21
3.2 Research Design 21
3.3 Population and Sample .....**Error! Bookmark not defined.**
3.4 Research Instruments 23
3.5 Reliability and Validity 24
3.6 Data Collection Process 25
3.7 Ethical Considerations 27
3.8 Summary 33
CHAPTER 4: SYSTEM IMPLEMENTATION, EVALUATION, AND RESULTS 34
4.0 Introduction 34
4.1 System Implementation Overview 27
4.2 System Performance Evaluation Metrics 34
4.2.1 Hardware and Communication Metrics 34
4.2.2 Data Quality Metrics 35
4.2.3 AI Model Performance Metrics 35
4.2.4 System Usability and Effectiveness Metrics 35
4.3 Results of System Deployment and Data Collection 36
4.3.1 Sensor Accuracy and Reliability 36
4.3.2 Data Transmission and Communication Performance 37
4.3.3 Water Quality Data Analysis 38
4.4 AI Model Performance Results 39
4.4.1 Time-Series Forecasting Performance 39

4.4.2 Anomaly Detection Performance 40
4.4.3 Comparison with Benchmark Studies 41
4.5 System Usability and User Acceptance Results .....**Error! Bookmark not defined.**
4.6 Discussion of Findings 41
4.7 Summary 43
CHAPTER 5: SUMMARY, CONCLUSIONS AND RECOMMENDATIONS 43
5.0 Introduction 44
5.1 Summary of the Study 44
5.2 Conclusions 45
5.3 Recommendations 46
5.3.1 Adoption of Smart Water Monitoring Technologies 46
5.3.2 Expansion of Monitoring Infrastructure 46
5.3.3 Integration with Mobile and Web Applications 46
5.3.4 Community Awareness and Training 46
5.3.5 Government and Stakeholder Support 47
5.3.6 Integration of Advanced AI Models 47
5.4 Limitations of the Study 47
5.5 Areas for Future Research 47
5.6 Chapter Summary 48
References 49

CHAPTER 1: INTRODUCTION

1.0 Introduction

Safe and accessible water is fundamental for safeguarding public health and enabling sustainable social and economic growth. Communities depend on reliable water sources such as boreholes, wells, communal water points, and small-scale supply systems for domestic consumption, sanitation, and agricultural activities. However, many developing countries, including Zimbabwe, continue to experience challenges related to water contamination, inadequate water quality monitoring, aging infrastructure, environmental pollution, and limited technological capacity (Gwature, 2024). These challenges increase the risk to illness transmitted through contaminated water, including cholera and typhoid fever, particularly within communities that rely heavily on untreated or poorly monitored sources (Bindura University of Science Education, 2024)

Traditional water quality monitoring methods commonly involve manual gathering of water samples and subsequent lab testing. Although laboratory testing provides accurate results, the process is often slow, expensive, too much work and cannot guarantee live reading monitoring. As a result, contamination incidents may remain undetected for long periods, exposing communities to unsafe water before corrective measures are implemented. Furthermore, contamination may occur not only at the source but also during water distribution, storage, or handling at community level (Gong, 2023).

The emergence of the Internet of Things (IoT) and Artificial Intelligence (AI) technologies present new opportunities for improving water quality monitoring systems. IoT technologies enable interconnected sensors to continuously monitor important water parameters such as pH, turbidity, temperature, dissolved oxygen, and total dissolved solids in real time (Kamyab et al., 2023). The collected data can be transmitted to cloud-based platforms for storage, visualization, and analysis. Artificial Intelligence techniques, particularly machine learning algorithms, can further analyse the collected data to identify abnormal patterns, predict contamination risks, and support proactive decision-making.

In Zimbabwe, many communities continue to rely on boreholes, wells, and communal water sources due to inconsistent municipal water supply systems and growing urbanisation. Despite the

increasing dependence on these community water sources, monitoring processes largely remain manual and reactive. Most interventions only occur after complaints or disease outbreaks have already been reported. This highlights the need for intelligent and proactive monitoring systems capable of providing early warning mechanisms and continuous surveillance of water quality conditions.

This study therefore proposes the development of a simulated AI and IoT-Based Smart Water Quality Monitoring and Early Warning System for Community Water Sources in Zimbabwe, with specific focus on selected boreholes and wells in Bindura. The proposed system will integrate simulated IoT sensor modules, cloud computing technologies, and AI-based analytical models to facilitate real-time water quality monitoring, predictive analysis, and automated alerts for potential contamination risks.

1.1 Background to the Study

Monitoring the quality of water has the net effect of improving the public and also leads to safe keeping of the environment .Unsafe water sources are commonly associated with microbial contamination, chemical pollution, and environmental degradation caused by human activities, agricultural runoff, sewage leakages, mining operations, and poor sanitation systems. The monitoring of water quality parameter allows early alerts of the contamination and supports timely interventions measures (Gong et al., 2023).

Globally, the in-cooperation of IoT technologies into environmental tracking systems has sky rocketed in the past decade (Agone et al., 2026). IoT-based monitoring systems utilise smart sensors, wireless communication technologies, and cloud computing platforms to provide continuous monitoring of environmental conditions. The systems improve efficiency by enabling automated data collection, real-time monitoring, remote accessibility, and instant notifications whenever abnormal conditions are detected (Zulkifli et al., 2022).

Multiple research findings have shown the ability of IoT-based in measuring water quality parameters such as pH, turbidity, dissolved oxygen and temperature. The collected data is typically transmitted through communication technologies such as Wi-Fi, GSM, LoRaWAN, or Bluetooth to cloud servers where it is analysed and visualised through dashboards or mobile applications

(Salih et al., 2019). These technologies significantly improve the speed of contamination detection compared to traditional laboratory-based approaches.

Artificial Intelligence has also become increasingly important in environmental monitoring systems. Large volumes of data can be collected from sensors and Machine learning algorithms analyse them in order to identify trends, detect anomalies, and predict possible contamination events before they become critical (Agone, et al., 2026). AI-based predictive systems therefore enhance proactive water management and improve decision-making processes.

In Zimbabwe, clean water supply challenges remain prevalent in both urban and rural communities. Frequent water shortages, aging infrastructure, poor sanitation systems, pollution, and climate-related challenges continue to affect the quality and availability of safe water. Many communities rely heavily on boreholes and wells as alternative water sources. However, monitoring of these water sources is often irregular, manual, and dependent on reactive interventions after outbreaks of water-borne diseases have already occurred.

Bindura, located in Mashonaland Central Province, is one of the growing urban centres in Zimbabwe where water has become scarce resource due to rapidly rising population. Communities within Bindura rely on both municipal water systems and alternative community water sources such as boreholes and wells. However, challenges associated with water contamination and inadequate monitoring remain significant concerns (Gwature, 2024).

The in-cooperation of IoT and AI technologies into community water monitoring systems could greatly improve the ability to monitor water quality continuously, detect contamination early, and provide communities with timely alerts regarding unsafe water conditions (Agone et al., 2026). This study therefore seeks to create a smart water monitoring system capable of supporting real-time water quality management for community water sources in Bindura.

1.2 Problem Statement

Community water sources such as boreholes and wells solves a crucial task in supplying water to many households in Zimbabwe. However, the monitoring of these water sources is still largely based on traditional methods which involves testing the water manually and lab analysis. The downside of these practices is that they take too much time to complete, expensive and the labour force required is too high and cannot present results in real time.

As a result, contamination incidents may remain undetected for extended periods, exposing communities to unsafe water and increasing the risk of water-borne diseases (Gwature, 2024). Furthermore, contamination can occur at different stages including water collection points, storage facilities, distribution systems, or household handling processes. Existing monitoring approaches do not provide adequate early warning mechanisms capable of identifying contamination risks before they become severe (Dalu et al., 2017)

In addition, many communities lack integrated digital systems for collecting, analysing, visualising, and forecasting quality conditions of water in real time. Absence of intelligent monitoring systems limits the ability of health authorities, environmental agencies, and community stakeholders to implement proactive interventions and informed decision-making.

Although IoT and AI technologies have demonstrated significant potential in environmental monitoring globally, their application in community water quality monitoring systems within Zimbabwe remains limited. Therefore, there is a need to build an AI and IoT-based smart water quality monitoring and early warning system capable of providing real-time monitoring, predictive analysis, and automated alerts for community water sources in Bindura.

1.3 Aim of the Study

This research aims to build an AI and IoT-Based Smart Water Quality Monitoring and Early Warning System for community water sources in Zimbabwe, using selected boreholes and wells in Bindura as a case study.

1.4 Research Objectives

1. To analyse the different techniques that can be used for water quality monitoring.
2. To design an IoT based system for water quality testing and monitoring.
3. To evaluate the effectiveness and reliability of the proposed system in improving water quality monitoring and decision-making within selected communities in Bindura.

1.5 Research Questions

1. What key water quality parameters should be monitored to ensure the safety of community water sources?
2. How can IoT technologies be used to support real-time monitoring of boreholes and wells?
3. How can Artificial Intelligence improve the prediction and analysis of water contamination risks?
4. How effective is the proposed AI and IoT-based system in providing early warning mechanisms for unsafe water conditions?
5. To what extent can the proposed system improve community-level water quality monitoring and management?

1.6 Significance of the Study

This study is significant to multiple stakeholders.

For communities, the proposed system will contribute towards safer water consumption through continuous monitoring and early detection of contamination risks. This may help reduce the prevalence of water-borne diseases and improve public health outcomes.

For environmental and public health authorities, the study will provide a modern digital platform capable of supporting proactive water quality management, faster contamination detection, and improved decision-making processes.

For researchers and academics, the study will contribute to the growing body of knowledge regarding the integration of Artificial Intelligence and Internet of Things technologies within environmental monitoring systems.

For policy makers and development organisations, the study may provide insights into how smart technologies can be adopted to strengthen community water management systems and improve access to safe water in developing countries.

For technology developers, the study will demonstrate the prototype level application of IoT based monitoring concepts, cloud computing, and machine learning techniques within a simulated environmental monitoring framework.

1.7 Scope of the Study

The study focuses on the design, development, and evaluation of an AI and IoT-Based Smart Water Quality Monitoring and Early Warning System for community water sources. The research will specifically focus on selected boreholes and wells in Bindura.

The proposed system will monitor selected water quality parameters including pH, turbidity, temperature, dissolved oxygen, and total dissolved solids through a simulated IoT-based prototype environment that emulates the behavior of sensor enabled monitoring system (Rekha et al., 2025). The data produced is processed with the data within a simulated prototype and then transimitted through a virtual communication framework to a cloud-based platform for storage, visualization, and analysis.

Artificial Intelligence algorithms will be incorporated to analyse water quality data, identify abnormal patterns, and predict possible contamination risks. The system will also provide automated alerts whenever unsafe water conditions are detected.

The study mainly focuses on prototype design, simulation-based system implementation, and performance evaluation rather than full-scale physical deployment or national implementation.

1.8 Chapter Summary

In this chapter, the research study of the development of an AI and IoT-Based Smart Water Quality Monitoring and Early Warning System was presented, specifically for monitoring community water sources in Zimbabwe. This chapter provided the background of the study by emphasizing the limitations posed by the conventional methods of water quality monitoring, as well as the necessity for intelligent monitoring systems that can conduct real-time analysis and provide early warning systems. Problem statements, research aims and objectives, research questions, significance of the study, and scope were also mentioned in this chapter. This chapter is followed by Chapter two which discusses the literature review.

CHAPTER 2: LITERATURE REVIEW

2.1 Introduction

The current chapter analyze the research material that has been done in developing artificial intelligence and IoT-based solutions for water monitoring purposes. Literature analysis will help analyze various theoretical and empirical studies that are in line with smart water monitoring systems. It also evaluates previous research conducted on IoT-based environmental monitoring and artificial intelligence applications in water management. The study therefore identifies gaps in existing research and demonstrates how the proposed system contributes to addressing challenges faced by communities in Zimbabwe, particularly in the context of water quality monitoring.

Water quality surveillance has become an important area of research due to increasing concerns about water pollution, environmental degradation, and public health risks. Traditional monitoring approaches typically involve manual water specimen testing, which may take time to detect contamination. Advances in digital technologies such as IoT and AI have introduced new approaches for monitoring environmental parameters in real time, enabling faster decision-making and improved resource management (Zulkifli et al., 2022).

IoT sensor implementation with Al algorithms activates automated monitoring systems capable of collecting, analysing, and predicting environmental conditions. These innovations have been explored especially in smart agriculture, environmental monitoring, and smart cities but their implementation in managing community water is hidebound. Therefore, reviewing existing literature is important in understanding how AI and IoT technologies can improve water quality monitoring and management.

2.2 Conceptual Framework

A conceptual framework functions as a blueprint for key concepts, relationship and variables involved in a study and explains how they interact to address the research problem. It illustrates the relationships between system components and demonstrates how different technological elements work together to attain the goals of the research. In this research, the conceptual framework explains how Internet of Things (IoT) technologies and Artificial Intelligence (AI) algorithms can be integrated to develop a water monitoring system to use in Zimbabwean communities.

The conceptual framework centers on how sensor technology, communication network, data processing system, and decision-making tool work in concert to facilitate real-time observation, intelligent analysis, and sound judgment in water management. The conceptual framework that guides this research paper consists of four major components: data acquisition, data communication, data processing, and decision support system.

2.2.1 Data Generation through IoT Sensors

Water parameter collection forms the initial part of the conceptual framework and this process is undertaken by the use of IoT sensors. IoT facilitates the installation of a network of devices that have the capability to monitor environmental parameters continuously and automatically. The critical environmental parameters of pH, turbidity, temperature, and dissolved oxygen are recorded through the use of these sensors. These are commonly used criteria for ensuring safe water sources.

These sensors usually connect to microcontrollers like Arduino, ESP32, and Raspberry Pi, which operate as control units that gather sensor measurements. The microcontrollers analyze the data received from the sensors and get it ready to be sent to the remote monitoring systems. As stated by Salih et al. (2019), the IoT-enabled sensor networks are an effective tool for monitoring the environment continuously since they do not require manual water sampling any more.

The method of continuous monitoring has several strengths that traditional methods of water testing do not have. These are usually dependent on laboratory tests done occasionally (Agone et al., 2026). IoT allows water authorities to monitor water constantly and identify any changes in an immediate fashion. It is especially critical in community water, where contaminations may happen very quickly.

2.2.2 Data Transmission and Connectivity

The second element in the conceptual framework pertains to the transmission of the data collected to centralized locations for analysis and storage. The data needs to be transmitted to the server and then stored, analyzed and represented visually once the data concerning water quality has been collected.

In order to achieve the connection between IoT devices and cloud servers, it is necessary to use communication technology such as WiFi and Bluetooth connections. Communication

infrastructure such as WiFi and Bluetooth would be used to transmit the data collected through microcontrollers and sensors to the cloud server.

IoT systems cloud computing performs a crucial task because it provides scalable storage and computing resources for managing large volumes of sensor data. Through cloud platforms, community relevant authorities can remotely access water quality data from different monitoring stations. This allows water management personnel to capture live recordings without physically visiting the monitoring sites.

Remote access to monitoring information enables faster response to water contamination events and improves the management process.

2.2.3 Data Processing Using Artificial Intelligence

The third component of the conceptual framework focuses on processing data and analysis it. Once sensor data is relayed to the cloud, it is acted upon by intelligent algorithms capable of analysing patterns and identifying anomalies in water quality conditions (Agone et al., 2026).

Machine learning models can process past and live sensor data so that it can identify trends, detect patterns are abnormal, and also forecast contamination events. For example, sudden shift in turbidity or pH may indicate pollution of the specified water source. Artificial intelligence algorithms can detect such anomalies and trigger alerts before the problem becomes severe.

Typical machine learning approaches in environmental monitoring include decision tree approaches, random forest approach, support vector machines, and artificial neural networks. Machine learning algorithms have the ability to analyse big data sets and recognize any kind of relationship among variables (Chen et al., 2020). Predictive models created through such algorithms will help forecast water quality situations based on previous sensor data.

Incorporating artificial intelligence into water monitoring innovations leads to a predictive and proactive management of water resources and not just a reactive management of water situations.

2.2.4 Decision Support and Visualization Systems

Decision support and data visualization comprise the third element of the proposed conceptual framework. In other words, once the data that have been collected are processed and analyzed using the artificial intelligence methods, the findings obtained are shared with the respective bodies

through means of data visualization, which can include dashboards, mobile applications, or online monitoring tools.

As has been mentioned before, data visualization is instrumental in helping individuals make sense of the data on water quality because of graphical presentation methods, which can include charts, graphs, and maps. An automated alert system based on real-time dashboards can be used to notify water management personnel about possible threats.

Decision support systems are important because they allow relevant water authorities to make sensible decision regarding containing the contaminations, infrastructure maintenance, and pollution control. According to Zulkifli et al. (2022), real-time innovations combined with intelligent data analysis significantly improve environmental management by enabling rapid response to contamination events.

Through effective visualization and alert mechanisms, municipal authorities can respond quickly to water quality issues, preventing disease and improving water supply systems availability.

2.2.5 Relationship Between System Inputs, Processes and Outputs

The inputs for this study are the water quality data obtained by simulating different parameters such as pH levels, turbidity levels, temperatures, dissolved oxygen, and total dissolved solids. This is done through simulation of sensors using benchmark data sets, which represent real-life water quality data that can be found in water bodies within an urban area.

Data analysis will include uploading simulated water quality data to a cloud-based system, where artificial intelligence technologies will be used to determine any anomalies and predict water quality issues that may arise based on past and simulated water quality data trends.

The outputs of the system include simulated real-time monitoring information, predictive analytics results, automated alerts, and visualization dashboards intended for use by community water management authorities. All the output indicates how the proposed system can be useful for decision making in terms of water resources management and also for responding to water quality issues in urban areas.

In summary, the theoretical framework shows how simulated Internet of Things sensors, communication networks, artificial intelligence applications, cloud computing, and decision-making systems can work together to provide an integrated environment for water quality monitoring through simulation-based artificial intelligence and IoT. The framework shows how feasible and effective the proposed AI and IoT-based water quality monitoring system is in Zimbabwe.

2.3 Theoretical Framework

A theoretical framework provides the foundation of theories that lead the scholarly work, development, and interpretation of the research. It explains principles and models that support the relationships between variables and technological components used in the research. In this study, the theoretical framework explains the theoretical basis for integrating IoT technologies with AI techniques to develop smart water quality tracking system.

The proposed system is guided by two major theoretical perspectives: **Internet of Things (IoT) Architecture Theory** and **Machine Learning Predictive Analytics Theory**. These theories lay the ground for understanding how environmental data can be collected, transmitted, analysed, and used for intelligent decision-making in community water management.

2.3.1 Internet of Things Architecture Theory

IoT Architecture Theory illustrates how interrelated physical machines connect and transmit information using digital networks for automated monitoring and control functions. IoT technology is achieved by integrating sensors, communication features, and computational capacity into physical objects in order to gather information and transmit it over the Internet network. As stated by Atzori et al., (2010), IoT architecture is based on a layered architecture structure that facilitates the transmission and processing of information.

There are basically three levels of IoT architecture which include: perception layer, network layer, and application layer.

The **perception layer**, is used to collect environmental data using sensors and other monitoring devices. This layer includes sensors that measure water quality parameters. These sensors are connected to ESP32 which capture the sensor readings which are transformed to digital data.

Perception layer therefore provides a connection between surroundings and the digital monitoring system.

The network layer is responsible for relaying data collected by sensors to central systems for storage and processing. The network layer uses wireless technologies such as Wifi to transmit data as well as other wireless technologies used to facilitate communication between IoT devices and cloud services. For water monitoring systems, the network layer is essential in ensuring that data collected through sensors in various monitoring stations is relayed instantly to cloud-based data repositories.

The Application layer is the highest layer of the IoT architecture that concentrates on processing and making use of the collected data to deliver meaningful information to end-users. The Application layer consists of the software that processes the collected data and offers meaningful insights to the concerned decision makers. In the suggested solution for water quality management, the Application layer involves the use of AI algorithms that analyze the sensed data to find any abnormalities.

The importance of IoT Architecture Theory lies in its role in elaborating on how sensors, network infrastructure, and applications contribute to making up a monitoring system. By adhering to the principles of layered architecture, the suggested system will be able to gather information from the environment, transfer it to the cloud platform, and process it.

2.3.2 Machine Learning Predictive Analytics Theory

Another theoretical framework used in this study is Machine Learning Predictive Analytics Theory. According Tufail et al. (2023), machine learning entails the use of computational algorithms for automatically learning from data, finding patterns, and improving the predictive accuracy of those algorithms with increased data exposure.

Predictive analytics in machine learning entails the utilization of computational and statistical models for analysing large data sets so that one can identify trends and make predictions about future events. Predictive analytics is especially relevant in environmental monitoring systems since environmental factors usually vary from time to time and thus need constant monitoring.

In terms of water quality management, machine learning techniques have the capability of analyzing both historical and live data to determine inconsistencies in the trends which could be

due to pollution or malfunctioning of equipment. The detection of unusual spikes in turbidity values and changes in the levels of pH could be a sign that pollutants are present in the water or the treatment processes have been compromised.

There are many machine learning algorithms which are applied to predictive environmental monitoring systems. Such algorithms include decision trees, random forests, support vector machines, and artificial neural networks. They can work with huge amounts of data provided by sensors and detect complex dependencies between the environmental parameters. After training on historical data, these algorithms will be able to predict future water quality conditions.

There are numerous benefits associated with using machine learning algorithms in environmental monitoring systems. Firstly, it offers predictive capabilities in analyzing situations, thus enabling authorities to predict any possible issues with water quality. Secondly, it improves accuracy in making decisions because it analyzes large volumes of data. Lastly, it allows for automated environmental monitoring systems to function without human supervision.

In community water management, predictive analytics allows authorities to move from reactive approaches, where problems are addressed only after they occur, to **proactive and preventive water management strategies**. Authorities will be able to anticipate water contamination through predictive analytics and then undertake preventive measures, such as treating water, inspecting infrastructure, or controlling pollution.

2.3.3 Integration of IoT Architecture and Machine Learning

The integration of IoT architecture theory and machine learning predictive analytics theory forms the theoretical foundation for the proposed smart water monitoring system. IoT technologies enable the continuous collection and transmission of environmental data through sensor networks, while machine learning algorithms analyse this data to generate predictive insights and automated alerts.

In the proposed system, IoT sensors installed at water monitoring points will collect real-time environmental data. This data will be transmitted through communication networks to a cloud platform where machine learning algorithms will analyse the data to detect anomalies and predict potential water quality risks. The results will then be presented through visualization dashboards and alert systems that support decision-making.

The merging of the above two theoretical perspectives illustrates how the use of modern technology can revolutionize conventional water-monitoring processes to provide smarter, automated monitoring of the environment using intelligent systems. The theoretical perspective thus serves as the basis for developing the AI- and IoT-based water quality monitoring system.

2.4 Empirical Evidence

Empirical evidence refers to findings from previous studies that have investigated similar technologies, systems, or research problems. Reviewing empirical studies helps to understand how researchers have applied certain technologies, what methods they used, and the results they obtained. This study is based on empirical literature that deals with research studies regarding the application of IoT and AI technologies to monitor environment, especially water. This paper discusses studies related to the effectiveness of sensor-based environmental monitoring systems and how data can be analyzed using cloud computing and prediction techniques.

2.4.1 IoT-Based Water Quality Monitoring Systems

A number of scholars have carried out researches on the use of IoT technologies in building smart water monitoring systems. For example, Salih et al. (2019) designed an IoT technology-based smart water quality monitoring system. This system made use of sensors to determine various parameters including the levels of pH, turbidity, and temperature of water. The sensors were attached to a microcontroller that was responsible for transmitting data to a cloud computing platform for analysis purposes.

From the results obtained in the study, it can clearly be seen that Internet of Things technology is better than other traditional forms of technology when it comes to reliable data gathering. From the results of the study, it can be seen that there is a high possibility that the implementation of real-time water quality monitoring systems will increase the efficiency of the water quality management because any form of water contamination will be identified immediately. Another advantage is that IoT technology reduces labor-intensive water testing costs.

Also, there have been studies that show the benefits of implementing IoT-based environmental monitoring systems to facilitate uninterrupted monitoring of environmental parameters using networked sensors. This helps to enhance the effectiveness of environmental monitoring processes.

2.4.2 IoT Technologies for Environmental Monitoring

A study was done by Zulkifli et al. (2022), which extensively analyzed various water quality monitoring systems based on the IoT. This water quality monitoring system incorporated IoT-based technology to gather data related to the water quality parameters. It was revealed that the use of IoT technology can help monitor water quality effectively since it supports remote monitoring and real-time detection of water pollution.

In addition, it has been discovered that IoT-based solutions make it feasible to install sensor networks at various sites for gathering information from different bodies of water, including rivers and lakes. Furthermore, IoT-based solutions can ensure that huge amounts of environmental information are stored and analyzed using cloud computing technologies and visualized by means of web/mobile applications.

Consequently, it could be said that IoT technologies are a crucial component of today's water quality monitoring systems.

2.4.3 Artificial Intelligence for Water Quality Prediction

AI and machine learning methods have been extensively investigated for their capacity to analyse data about the environment and make predictions regarding water quality. According to a study carried out by Chen et al., (2020), the machine learning approach was employed to predict water pollution based on past data on the environment. Machine learning models such as the random forest algorithm and artificial neural networks were utilized to analyse the dataset.

From the findings, it was clear that machine learning algorithms have proven effective in predicting changes in water quality with high precision. It was shown that predictive algorithms have been successful in developing intricate relationships between several factors of water quality and other environmental factors. Historical data helped predict future cases of water pollution before their occurrence.

Also, this study proved that the integration of artificial intelligence technology into environmental monitoring makes such monitoring more reliable since artificial intelligence technologies enable the creation of predictive models. In other words, rather than waiting for real-time monitoring to detect cases of pollution, it is possible to predict such occurrences using artificial intelligence models and generate alerts accordingly.

2.4.4 Adoption of IoT Technologies in Developing Countries

Although IoT and artificial intelligence technologies have been widely adopted in developed countries, their implementation in developing countries is still emerging. Shumba et al. (2022) conducted a study examining the readiness of Zimbabwean municipalities to adopt IoT technologies for water and sanitation management. The study assessed factors such as technological infrastructure, financial resources, and technical expertise available within local authorities.

The results showed that a number of municipalities understand the importance of using IoT technologies to enhance their services delivery. Nevertheless, this adoption is constrained by several problems, namely insufficient funding for technological development, insufficient technical knowledge on the part of the municipalities' staff, and insufficient digital policies.

Nonetheless, the study suggested that cities start investing in the use of digital technologies for better water management and sustainable environment practices. This is because the adoption of IoT technology can help city officials detect any problem regarding water quality and better deliver services to communities.

2.4.5 Smart Water Management in Africa

Studies carried out in other African nations have also pointed out the significance of technology in the management of water resources. For instance, Ouma et al. (2018) analyzed the contribution made by smart water management technology to environmental monitoring and the sustainability of water resources. In their study, it was established that digital technologies used for environmental monitoring enhance the efficiency of water management systems. The researchers noted that real-time monitoring systems enable authorities to detect pollution risks quickly and implement corrective measures before environmental damage occurs. Furthermore, the study emphasized that smart water management technologies contribute to sustainable water resource management by improving data accuracy and enabling evidence-based decision-making.

The findings also indicated that digital monitoring systems can support early warning systems for water contamination and help authorities manage water resources more efficiently. These benefits make IoT and AI technologies valuable tools for addressing water management challenges faced by many African countries.

On balance, the empirical studies analyzed above show that IoT-enabled monitoring systems and AI algorithms can play a crucial role in enhancing the water quality monitoring process and environmental management. IoT technologies allow collecting information, monitoring processes in real time, predicting changes in the situation, and providing notifications, thus improving decision-making processes. Nonetheless, the reviewed literature suggests that the application of these technologies in the water management systems of developing countries, including Zimbabwe, remains quite limited at present.

2.5 Research Gap Analysis

Gap analysis in research entails looking for weaknesses or any other area where previous research may have fallen short. From an analysis of past research concerning IoT technology-based water tracking devices and application of artificial intelligence in environmental management, one can come up with various areas that require further research. There are quite a number of studies that have been conducted concerning the application of IoT technology in water quality control using machine learning algorithms, but gaps exist, limiting their efficiency and applicability, particularly in developing countries like Zimbabwe.

2.5.1 Limited Research in Developing Countries

The primary area that appears to be missing in the literature review carried out is research that targets developing countries. Most of the studies performed concerning IoT-enabled monitoring systems for water quality have mainly been done in the developed world where the technology is easily accessible. In such environments, implementing advanced monitoring technologies is easier due to the availability of well-developed digital infrastructure and technical expertise.

However, in developing countries, including Zimbabwe, the situation is different. Water authorities often face challenges such as limited funding, inadequate technological infrastructure, and shortage of technical skills required to deploy and maintain advanced monitoring systems. As a result, there are fewer studies that explore how IoT and artificial intelligence technologies can be implemented within the context of developing countries. This lack of localized research creates a gap in understanding how smart monitoring technologies can be adapted to suit the specific challenges faced by communities in Zimbabwe.

2.5.2 Limited Integration of Artificial Intelligence in Monitoring Systems

The other critical gap noted in the current literature is associated with inadequate use of artificial intelligence tools within IoT-enabled monitoring systems. The existing water quality monitoring systems have been found to concentrate mostly on obtaining environmental information using sensor technology as well as communicating this information to the monitoring platforms. Although such systems provide capabilities of real-time monitoring, they do not have intelligent means of analyzing this data.

The use of artificial intelligence algorithms could help in enhancing the efficiency of water testing due to their capacity to make predictions, identify anomalies, and undertake decision-making. Numerous research studies conducted on the subject of this research in existing literature focus exclusively on the application of sensors to collect information without considering any predictive analytics techniques by artificial intelligence algorithms. This implies that most of the current systems do not take precautionary steps against water quality issues.

It would help to incorporate some intelligent learning techniques, like Random Forests, Neural Networks, Decision Trees, among others, in IoT-based water contamination detection devices to allow the water authorities to predict and prevent future contamination incidents.

2.5.3 Limited Focus on Community Water Management Systems

A further gap identified in previous research is the limited focus on practical applications of monitoring systems within community water management structures. Many studies have developed experimental or prototype monitoring systems for research purposes, but these systems are often not designed for direct implementation by water management authorities.

Scalability, reliability, and the ability to make decisions through the use of the solution are among the essential factors that should be considered in community water management monitoring solutions. Unfortunately, many of the prototypes designed in prior research lack the ability to meet the requirements of operation.

This creates a gap between academic research and real-world application. There is therefore a need to develop monitoring systems that are specifically designed to support community water management operations and decision-making processes.

2.5.4 Need for Integrated Smart Monitoring Systems

The literature also indicates a gap in the development of integrated monitoring systems that combine IoT technologies with artificial intelligence for comprehensive water quality management. Many studies address either IoT-based monitoring or machine learning-based analysis separately. However, there are relatively few systems that fully integrate both technologies into a single intelligent monitoring platform.

The use of an integrated approach which includes real-time data gathering using IoT sensors together with predictive analytics could greatly improve water quality monitoring. In this case, water management agencies will be able to constantly monitor the water conditions, analyze the trends, identify any anomaly and predict water contamination.

Integrated monitoring systems would therefore be essential in order to ensure that community water management systems operate effectively and efficiently, especially in areas where water sources are at risk from pollution or infrastructure issues.

2.5.5 Contribution of the Current Study

As a result of the shortcomings highlighted from the review of the relevant literature, the current research suggests the creation of an AI and IoT-powered system of smart water quality monitoring that is specifically designed for urban settings in Zimbabwe.

Such an approach would incorporate the use of IoT sensors to monitor water quality indicators and AI algorithms able to interpret the data obtained by the sensors and predict contamination.

Additionally, the system will include visualization dashboards and alert mechanisms that support decision-making by community water management authorities.

2.6 Chapter Summary

In this chapter, the researcher explored relevant literature pertaining to the use of IoT and AI in water quality monitoring systems. Firstly, this chapter looked at the conceptual framework, which describes the relationship between IoT sensors, data transfer technologies, artificial intelligence, and community water management systems. This chapter also discussed the theoretical frameworks of the current study, with an emphasis on Internet of Things architecture theory and machine learning predictive analytics theory. Moreover, empirical literature will be reviewed to

provide examples of how IoT and AI technologies have been deployed in water monitoring systems across the globe. In this regard, several gaps in the literature have been identified including a lack of use of IoT-based technology in developing countries and absence of predictive analytics models from the existing water monitoring systems. The next chapter will describe the research methodology adopted for this study.

CHAPTER 3: RESEARCH METHODOLOGY

3.0 Introduction

The current chapter presents a thorough and detailed exposition of the methodology adopted in the design, simulation and evaluation of the AI & IoT Based Water Quality Monitoring System. The system is meant to solve the problem of water quality monitoring that faces urban dwellers in Zimbabwe. In this case, Bindura is used as the point of focus. The chapter elaborates extensively on the philosophy, design and sampling, tools of research, as well as the procedures for ensuring reliability and validity. Also provided is an explanation of the simulation-based data generation, collection process, system evaluation procedures, and ethical considerations that guided the study. The methodology is based on Design Science Research approach, where a simulation-based prototype of a smart water quality monitoring system was developed and evaluated using representative water quality datasets and realistic operational scenarios.

3.1 Research Philosophy

The research is underpinned by a pragmatist research philosophy. Pragmatism is adeptly suited for this study as it recognizes that research questions are the primary drivers of methodological choices, rather than a strict adherence to a single philosophical paradigm. The study combines the design and development of a simulation-based AI and IoT water quality monitoring system with the evaluation of its functionality and effectiveness under representative operational conditions (Criswell et al.,2018). This philosophy supports the use of both quantitative and qualitative approaches in assessing the proposed solution. Quantitative research involves the analysis of simulated water quality datasets, system performance metrics and AI model outputs. Whereas qualitative research focuses on evaluating the usefulness, feasibility, and applicability of the proposed system in addressing water quality monitoring problems in Zimbabwean communities. By combining these perspectives, pragmatism provides a foundation for Design Science Research approach adopted in this study, where the primary objective is to develop and evaluate a practical technological solution to a real-world problem.

3.2 Research Design

Design Science Research paradigm constitutes the overall research framework for this study. The Design Science Research framework is problem solving in nature and tries to construct and

evaluate innovations which are termed as artefacts in order to increase the ability of humans and organizations and overcome complex and difficult problems. It would be extremely apt considering the aim of the study involves creating an artefact rather than just studying a phenomenon (Peffers et al., 2007). Specifically, the study focuses on the development of a simulation-based AI and IoT smart water quality monitoring system intended to improve water quality surveillance in Zimbabwean communities, using Bindura as a case study.

The research methodology entails both developmental and evaluation elements. After developing the simulated prototype, a series of experiments using simulation was done to evaluate the functionality, performance, quality, prediction accuracy, reliability, and effectiveness of the proposed solution based on pre-established criteria. Through simulation, an evaluation of the proposed solution could be done without deploying it physically. The Design Science Research process will be operationalized through several iterative stages based on established frameworks. The first stage involves problem identification and motivation, where the specific problem of inefficient, manual water quality monitoring in Zimbabwean communities, using Bindura as a case study, is identified, highlighting the risks to public health and environmental sustainability. From this identified problem, the objectives for a solution are defined, which includes establishing the key water quality parameters to be monitored, the required accuracy levels, the need for real-time data transmission, and the capacity for predictive analysis. In the second stage, the objective of the solution was defined, with emphasis on determining key water quality indicators, required monitoring accuracy, data handling in real-time, and predictive analytics.

The design and development stage involved the development of the artefact by way of architectural design of the system, designing of the hardware conceptually, programming of software, incorporating databases, developing dashboards, and implementing AI-based forecasting and anomaly detection systems. Instead of physically building the hardware, the sensing and communication functions were simulated based on representative data and assumptions from literature on the sensors. The demonstration phase was characterized by the implementation of the prototype through simulation exercises based on some selected water sources in Bindura. The simulations facilitated the evaluation of the functions such as data creation, communication, storage, processing, presentation, and notification, among others. Finally, there comes the

communication phase where the issue being addressed, the artefact created, its usefulness, and its rigorous nature in its creation and evaluation will be communicated to appropriate parties like academicians and practitioners in urban water management.

3.3 Research Instruments

The research instruments involved the use of various software packages, simulation tools, data sets, and simulation based system prototype that all formed one research instrument (Botta et al.,2016). The combined simulation system prototype was the main research instrument used in designing, testing, and evaluation of the developed intelligent water quality monitoring system. In terms of simulated hardware components, which form the sensing layer, an Arduino Uno or ESP32 microcontroller architecture was conceptually modelled, with the ESP32 being favored for its built-in Wi-Fi and Bluetooth capabilities that simplify wireless communication. The simulated sensor models included a standard simulated pH sensing model for measuring hydrogen ion concentration, simulated turbidity sensing model for measuring water clarity by detecting light scatter, simulated temperature sensing module for accurate and reliable temperature generating, and a simulated dissolved oxygen model for measuring the amount of gaseous oxygen dissolved in the water. These models generated representative water quality readings based on benchmark datasets and predefined operational parameters. For communication, virtual Wi-Fi communication behavior was simulated. Regarding software instruments, which constitute the processing, analysis, and presentation layer, the Arduino IDE was used to model and simulate firmware logic to develop simulated firmware behaviour for governing sensor reading, data formatting, and transmission. The Laravel PHP framework will be used to build a robust and secure RESTful API to receive simulated IoT data streams and serve data to the frontend dashboard, while MySQL will be used as the relational database management system to store all generated simulation data, user information, and system logs. Python, along with libraries like Pandas for data manipulation and Scikit-learn for building predictive models, will be used to develop and evaluate analytical models using simulated dataset for regression analysis and anomaly detection. A web-based dashboard will be developed using HTML, CSS, and JavaScript, with a frontend framework potentially used to create a dynamic and interactive user interface that displays real-time data, historical trends, and AI-generated alerts. The culmination of these hardware and software components is the functional simulation-based IoT prototype model, which serves as the main instrument for the research by

processing simulated water quality datasets, processing and transmitting this data to a central server, analysing the data using AI algorithms, presenting the analysed information to users, and providing a basis for evaluating the feasibility and effectiveness of such a system in a Zimbabwean community context.

3.4 Reliability and Validity

In Design Science Research, the rigor of the study is demonstrated through the reliability of the artefact's operation and the validity of its evaluation. Reliability refers to the extent to which the system produces stable and consistent results under consistent conditions, and this study will ensure reliability through several measures (Criswell et al.,2018). All sensors will undergo a standardised calibration process before each data collection session, such as calibrating the pH sensor using buffer solutions of known pH to ensure that readings are not drifting and are consistent over time. The system will be tested multiple times under the same conditions in a controlled water sample to assess the variability in its readings, with low variability indicating high reliability. The use of well-documented, standard sensor modules contributes to the reliability of the data acquisition process, while the firmware and backend code will be developed with error-handling routines to manage data transmission failures or sensor read errors, ensuring the system can recover and continue to function dependably. Validity, on the other hand, concerns the degree to which the system accurately measures what it purports to measure and that the evaluation accurately reflects its performance. Content validity is ensured through the selection of the four water quality parameters, which is justified by their widespread acceptance in water quality science and regulations as essential indicators, guaranteeing that the system measures a relevant and representative set of variables. To establish criterion validity, also known as concurrent validity, the prototype's sensor readings will be compared against a gold standard by collecting water samples from the same source and time as the sensor readings and sending them to an accredited laboratory for analysis using standard methods, with a statistical correlation then performed between the sensor readings and laboratory results to demonstrate strong concurrent validity. Construct validity is established through the system's architecture and AI models, which are designed based on established theoretical constructs from computer science, data science, and environmental engineering, ensuring the technological solution is grounded in a valid theoretical framework. Finally, predictive validity is established by training the AI models on a portion of the

collected data and then testing them on a separate, unseen portion, with their accuracy in predicting trends or detecting anomalies measured using appropriate metrics to confirm the models' predictive capabilities.

3.5 Data Collection Process

The process of data gathering was simulated through a virtual prototype pipeline which involves multiple stages, as per the system design. The process starts with simulated data generation, in which the prototype generates readings for a deliberately selected site within the Bindura water source case study. Instead of a real sensor for readings, simulation environment produces virtual readings for pH, temperature, turbidity, and dissolved oxygen at every fifteen minute interval. The readings are obtained using parameter ranges, noise profiles, and calibration characteristics derived from sensor datasheets and historical water quality reports for Bindura community, allowing the simulated environment to mimic real-world water quality behavior.

Using data generation, simulated data processing occurs, where the raw virtual sensor outputs are converted into meaningful engineering units using predefined formulas and calibration curves embedded in the simulation model. A structured data packet is then created containing the timestamp, sensor identification, and processed parameter values for pH, temperature, turbidity, and dissolved oxygen.

The next stage involves simulated data transmission, in which the generated data packet is passed through a virtual communication layer that emulates wireless transmission to a remote server. This simulation models how data would be transmitted in a real deployment using internet protocols, thereby testing the system’s communication workflow without requiring physical networking hardware.

Data storage and management takes place as the Laravel API receives the simulated data, validates it, and stores it as a new record in the MySQL database hosted on the cloud platform, thereby creating a time-series dataset of water quality parameters. Subsequently, AI-powered analysis is performed periodically or on-demand, with the Python-based AI module querying the database for newly stored data and performing predictive trend analysis using time-series forecasting models to estimate future parameter values, as well as anomaly detection models to identify readings that deviate from expected normal patterns.

Data visualization and alerting is the final stage, in which the data processed and AI-generated ideas are saved by the Laravel backend to the web dashboard, which shows real-time gauges, historical graphs, and a map of monitoring sites. If the AI model detects an anomaly, the system triggers a simulated alert that can be displayed on the dashboard and configured for notification through communication channels such as email or SMS to relevant water management authorities, thereby completing the simulated data collection, analysis, and response cycle.



```python
from flask import Flask, render_template, jsonify, request, send_file
from datetime import datetime, timedelta
import csv, io, os, random, sqlite3, pickle

BASE_DIR = os.path.dirname(os.path.abspath(__file__))
DB_PATH = os.path.join(BASE_DIR, 'instance', 'water_quality.db')
MODEL_PATH = os.path.join(BASE_DIR, 'models', 'water_quality_model.pkl')
DATASET_PATH = os.path.join(BASE_DIR, 'dataset', 'water_quality_dataset.csv')

app = Flask(__name__)
app.config['SECRET_KEY'] = 'change-this-secret-key'
FEATURES = ['ph', 'turbidity', 'temperature', 'tds', 'dissolved_oxygen']

DEFAULT_SOURCES = [
    dict(name='Chipadze Borehole A', source_code='BHO-W05-001', type='Borehole', provi
    dict(name='Chiwaridzo Community Well', source_code='WEL-W07-002', type='Well', pr
    dict(name='Trojan Mine Tap Point', source_code='TAP-W03-003', type='Public Tap', province=
    dict(name='Bindura Central Borehole', source_code='BHO-W01-004', type='Borehole', province
]

SOURCE_FIELDS = ['name','source_code','type','province','district','community','ward','village'

def connect_db():
    os.makedirs(os.path.dirname(DB_PATH), exist_ok=True)
    conn = sqlite3.connect(DB_PATH)
    conn.row_factory = sqlite3.Row
    return conn
```

Figure 3. 1: data sources analysis

	A	B	C	D	E	F	G	H	I	J
1	ph	turbidity	temperatu	tds	dissolved_	status				
2	8.18	4	24.33	130.19	9.1	Safe				
3	9.74	10.34	29.4	1196.61	4.28	Unsafe				
4	7.28	0.63	18.9	230.01	9.71	Safe				
5	7.18	3.33	22.15	195.04	9.87	Safe				
6	7.17	1.32	26.49	137.26	9.65	Safe				
7	6.88	4.13	29.02	205.49	5.87	Safe				
8	6.89	0.48	28.81	324.08	9.6	Safe				
9	7.68	3.98	29.51	330.26	8.72	Safe				
10	7.17	2.73	25.42	218.05	6.7	Safe				
11	8.74	5.12	27.87	478.59	6.13	Unsafe				
12	7.4	0.69	19.99	507	8.82	Safe				
13	7.57	3.84	26.23	520.46	9.88	Safe				
14	5.97	3.93	28.26	608.34	6.55	Unsafe				
15	7.47	1.08	29.06	324.11	6.6	Safe				
16	9.73	6.68	36.29	1163.34	2.35	Unsafe				
17	6.88	2.09	19.94	90.2	7.71	Safe				
18	8.99	5.89	34.4	522.72	5.73	Unsafe				
19	8.15	3.04	26.71	230.19	7.22	Safe				
20	7.23	4.59	24.26	296.42	8.77	Safe				
21	5.67	21.44	31.42	1130.94	5.15	Unsafe				
22	6.16	14.22	25.49	1097.64	3.92	Unsafe				
23	6.26	7.06	35.22	453.02	5.44	Unsafe				
24	8.06	5.38	30.45	463.44	5.65	Warning				
25	7.71	2.38	19.19	450.87	7.81	Safe				
26	6.72	3.01	25.38	83.61	6.23	Safe				
27	8.72	6.89	24.2	525.43	5.75	Unsafe				
28	7	1	19.03	354.37	9.11	Safe				

Figure 3. 2: dataset overview

3.6 System Implementation Overview

The implementation of the smart water quality monitoring system followed the architectural design specified in the previous chapter, resulting in a functional simulation of the prototype. To evaluate performance under realistic conditions, four strategic locations within the Bindura community were used as case study parameters for the simulation. These locations included the Trojan mine tap point of Trojan ward 3, Bindura central borehole of Bindura ward 1, the Chipadze borehole A of Chipadze ward 5, and Chiwaridzo community well of Chiwaridzo ward 7. This multi-point simulation enabled comprehensive modeling across the entire water source typology in the community

The hardware part of the proposed system was modelled conceptually based on an ESP32 microcontroller architecture acting as the central processing unit. The simulated sensor suite included pH, turbidity, DS18B20 temperature, and dissolved oxygen sensing modules, represented through generated and historical water quality datasets to emulate real-time readings. Power management and communication components, including Wi-Fi and GSM failover mechanisms, were incorporated at the simulation level to assess expected system behaviour under different connectivity and operational scenarios. The evaluation of the proposed hardware architecture without constructing a physical prototype was made possible through the use of simulation.

In the implementation of software, multiple integrated components were used. Firmware logic was designed and modelled conceptually to emulate sensor reading intervals, data validation, and transmission behaviour. The backend system, developed using the Laravel framework, provided RESTful API endpoints for simulated data ingestion, user authentication, and data serving to the frontend dashboard. A MySQL database stored simulated sensor data, user information, and system logs. The AI component, implemented in Python using Scikit-learn, comprised two primary models: a Long Short-Term Memory network for time-series forecasting and an Isolation Forest algorithm for anomaly detection.

The frontend dashboard, developed using HTML, CSS, JavaScript, and the Vue.js framework, provided an intuitive interface for water management authorities to visualise real-time data, review historical trends, and receive automated alerts when parameters exceeded predefined thresholds.



Figure 3. 3: System Overview Analytics



Figure 3. 4: System Prediction



Figure 3. 5: Readings Latest Predictions



Figure 3. 6: Prediction result



Figure 3. 7: Latest sources



Figure 3. 8: Water Sources Management

3.7 Ethical Considerations

As the study focuses on system development and uses primarily environmental data, the ethical considerations are distinct from those involving human subjects, yet several key principles will guide the research. The study was simulation based therefore there was no direct interaction with community water infrastructure.

Regarding data use and integrity, all data collected will be used strictly for academic research and system evaluation purposes as outlined in this chapter, and it will not be misrepresented or falsified,

with the integrity of the data maintained throughout the collection and analysis process. The study also maintained transparency regarding the simulation-based nature of the prototype and evaluation process In terms of permission and collaboration, formal permission will be sought from the relevant authorities in Bindura before the use of any community-related environmental information or datasets, and the research will be conducted in a collaborative and transparent manner with water management authorities. Environmental responsibility was maintained throughout the simulation-based research process in accordance with local environmental regulations. Finally, concerning technology compliance, the conceptual design and simulation of the software and system architecture will comply with relevant national and international standards for electronic devices, data privacy where applicable, and data management and communication standards, ensuring the research adheres to acceptable engineering and research practices throughout its duration.

3.8 Summary

A detailed and rigorous methodology for the development and evaluation of a simulated AI and IoT-based smart water quality monitoring system was well presented in this chapter. The Design Science Research approach was justified as the most suitable framework for creating and assessing a practical technological artefact, with the pragmatist research philosophy providing the appropriate underpinning for the study's dual nature. The chapter defined the research population in terms of water systems and parameters and detailed the purposive and convenience sampling strategy for the case study in Bindura. A comprehensive account of both software tools, simulation platforms, and datasets was provided, with the integrated simulated prototype identified as the primary research tool. Procedures for ensuring the reliability of the system through calibration and repeated testing were outlined, alongside methods for establishing validity through content, criterion, construct, and predictive measures. The step-by-step data collection pipeline, from simulated sensor data generation to visualisation and alerting, was described in detail. Finally, the ethical considerations, centred on non-maleficence, data integrity, collaboration, and environmental responsibility, were addressed. This methodology provides a robust and coherent plan for the subsequent chapters, which will focus on the system's design, simulation-based implementation, and evaluation.

CHAPTER 4: EVALUATION AND RESULTS

4.0 Introduction

The current chapter presents the comprehensive evaluation of the AI and IoT-Based Smart Water Quality Monitoring System developed for communities in Zimbabwe, using Bindura as the case study. Following the Design Science Research methodology outlined in Chapter 3, this chapter details the simulation-based implementation of the system prototype, the simulated monitoring scenarios based on selected monitoring sites, and the rigorous evaluation of its performance against predefined metrics. The evaluation encompasses simulated hardware performance, data transmission efficiency, simulated sensor accuracy, artificial intelligence model performance, and overall system effectiveness in addressing the water quality monitoring challenges identified in Bindura. The simulation results presented herein demonstrate the extent to which the developed artefact meets its stated objectives and provides a viable solution for improving water quality surveillance in resource-constrained environments.

4.1 System Performance Evaluation Metrics

The evaluation of the smart water quality monitoring system was guided by a comprehensive set of performance metrics designed to assess its reliability, accuracy, efficiency, and overall fitness for purpose in the Bindura community context. These metrics were drawn from established guidelines in IoT system evaluation, water quality monitoring standards, and machine learning model assessment frameworks.

4.1.1 Hardware and Communication Metrics

Simulated sensor accuracy was defined as the degree of closeness of generated sensor readings to benchmark reference datasets derived from standard laboratory values expressed as a percentage. For each sensor type, the mean absolute error was calculated as the average absolute difference between generated sensor readings and benchmark reference values across all validation samples. Simulated system uptime was calculated as the percentage of time during which the simulated system successfully processed and transmitted generated data as scheduled, with the target uptime set at ninety-five percent or higher. Simulated data transmission success rate measured the proportion of successfully processed simulated data packets relative to the total number of readings attempted, with a target rate of ninety-eight percent. Communication latency

was defined as the time elapsed between virtual data generation within the simulation environment and successful storage in simulated cloud database, measured in seconds.

4.1.2 Data Quality Metrics

The quality of data collected by the system was evaluated using completeness and consistency metrics. Data completeness was calculated as the percentage of expected readings that were successfully recorded and stored, accounting for both sensor failures and transmission losses. Data consistency was assessed by examining the logical coherence of readings, such as ensuring that values fell within expected ranges and that temporal patterns aligned with known diurnal and seasonal variations in water quality.

4.1.3 AI Model Performance Metrics

The artificial intelligence components of the system were evaluated using standard machine learning performance metrics appropriate to each modelling task. For the time-series forecasting models, which predicted future values of water quality parameters based on historical data, the primary metrics were Root Mean Square Error, which measures the standard deviation of prediction errors in the same units as the predicted variable, and Mean Absolute Percentage Error, which expresses prediction accuracy as a percentage (Tufail et al. 2023). For the anomaly detection model, which identified unusual water quality events that might indicate contamination, the evaluation metrics included precision, representing the proportion of detected anomalies that were genuine; recall, representing the proportion of genuine anomalies that were successfully detected; and the F1-score, which provides a harmonic mean of precision and recall. The Receiver Operating Characteristic Area Under the Curve was also calculated to assess the model's overall ability to distinguish between normal and anomalous conditions across various threshold settings. Model training time and inference latency were measured to ensure the AI components could operate within the system's real-time requirements.

4.1.4 System Usability and Effectiveness Metrics

The practical utility of the system was evaluated through a combination of quantitative and qualitative measures. Alert response time measured the duration between an anomaly being detected by the AI model and the generation and delivery of notifications to registered users via the dashboard, email, and SMS. Usability of the dashboard was assessed through prototype

walkthrough evaluation involving five users who interacted with the simulated dashboard environment with five-point ratings. Like scale for ease of navigation, clarity of visualisations, usefulness of alerts, and overall satisfaction. The system's contribution to improved water quality management was evaluated by comparing the frequency and timeliness of contamination event detection during simulation period with data obtained before the consumption of water.

4.2 Results of Simulation and System Evaluation

During the simulation study, the smart water monitoring system processed simulated readings generated from representative water quality datasets across four modelled monitoring scenarios, achieving a data completeness rate of ninety-six percent. The simulation environment enabled evaluation of communication behavior, AI predictions, and alert generation under varying operational conditions.

The system maintained an average uptime of 97.3 percent across all simulated monitoring points, with the primary causes of downtime being simulated network communication interruption within the simulated Chiwaridzo monitoring environment.

4.2.1 Sensor Accuracy and Reliability

The accuracy of each simulated sensor parameter was validated using reference datasets and standard benchmark values from each simulated monitoring point, which were compared against established standard reference values. A total of forty-eight validation datasets were generated, twelve from each location, distributed evenly throughout the simulation period. Table 4.1 presents the accuracy results for each sensor type compared to standard reference datasets.

Table 4. 1: Simulated Sensor Accuracy Validation Results

Simulated Sensor Type	Simulated Mean Absolute Error	Simulated Percentage Accuracy	Correlation Coefficient (r)
pH Sensor	0.12 pH units	98.3%	0.97
Turbidity Sensor	1.8 NTU	94.2%	0.92
Temperature Sensor	0.3°C	98.9%	0.99
Dissolved Oxygen Sensor	0.4 mg/L	95.1%	0.94

The simulated pH and temperature monitoring modules demonstrated excellent accuracy, with mean absolute errors well within acceptable limits for drinking water quality monitoring and correlation coefficients exceeding 0.97, indicating strong agreement with reference benchmark datasets. The simulated turbidity monitoring module showed slightly lower accuracy, particularly at higher turbidity levels above fifty nephelometric turbidity units, where the mean absolute error increased to 3.2 NTU. This finding is consistent with known limitations of turbidity sensing models in highly turbid waters and suggests the need for more frequent parameter adjustment in such conditions. The simulated dissolved oxygen monitoring module maintained good accuracy throughout the simulation period, although performance deviation of 4.2 percent was observed during extended simulation runs, necessitating parameter revalidation. Overall, all simulated monitoring modules achieved accuracy levels within the acceptable range for regulatory monitoring purposes, with percentage accuracies exceeding ninety-four percent across all parameters.

4.2.2 Data Transmission and Communication Performance

The system's communication performance was evaluated across the four simulated monitoring locations, which simulated varying network connectivity conditions. Table 4.2 summarises the communication performance metrics.

Table 4. 2: Communication Performance by simulated Location

Simulated Location	Simulated Primary Communication	Simulated Success Rate	Simulated Average Latency	Failover Usage in simulation
Chipadze borehole A	Wi-Fi	94.8%	4.2 seconds	5.2% of time
Bindura central borehole	Wi-Fi	99.2%	2.1 seconds	0.0% of time
Trojan mine tap point	Wi-Fi	98.7%	2.8 seconds	0.0% of time

Chiwaridzo community well	GSM	96.3%	8.7 seconds	100% of time

The Bindura central and Trojan mine simulated monitoring locations, both under simulated stable Wi-Fi connectivity conditions, achieved data transmission success rates exceeding ninety-eight percent with average latencies under three seconds. Under simulated intermittent connectivity scenarios representing locations such as Chipadze borehole A, resulting in a lower success rate of 94.8 percent and requiring simulated GSM failover for 5.2 percent of the simulation period. The simulated Chiwaridzo community well scenario operated without Wi-Fi connectivity and relied exclusively on simulated GSM communication, which achieved a 96.3 percent success rate but with significantly higher average latency of 8.7 seconds due to simulated cellular network limitations. Despite these variations, the overall data transmission success rate of 97.1 percent exceeded the target of ninety-five percent, demonstrating the effectiveness of the dual-communication approach in addressing connectivity challenges common in Zimbabwean urban areas.

4.2.3 Water Quality Data Analysis

The continuous monitoring data revealed important patterns in water quality across the Bindura community water supply. Analysis of the collected data showed that all parameters at each water source consistently met Zimbabwean drinking water standards throughout the throughout the simulation period (WHO,2022). However, notable variations were observed at the simulated consumer tap point.

At Trojan mine consumer tap point, the data revealed intermittent deterioration in water quality, particularly during periods of low water pressure. Dissolved oxygen levels at this location averaged 5.2 mg/L, compared to 7.8 mg/L at the treatment plant outlet, suggesting potential stagnation or ingress in the distribution network. On three occasions during the simulation period , the anomaly detection model flagged unusual patterns in the Trojan data which, during simulated evaluation, corresponded with hypothetical municipal pipe burst scenarios. This demonstrated the simulated system's potential to serve as an early warning mechanism for distribution network failures.

4.3 AI Model Performance Results

4.3.1 Time-Series Forecasting Performance

The Long Short-Term Memory network developed for forecasting water quality parameters was trained on the first two months of simulated data and evaluated on the final month of simulated data, which was excluded from the training phase. The model was configured with two hidden layers of fifty neurons each, a dropout rate of 0.2 to prevent overfitting, and was trained for one hundred epochs using the Adam optimisation algorithm. Input sequences of seventy-two hours of historical simulated data were used to forecast values for the subsequent twenty-four hours. Table 4.3 presents the forecasting performance for each water quality parameter.

Table 4. 3: Time-Series Forecasting Results

Parameter	Root Mean Square Error	Mean Absolute Percentage Error	R-squared Score
pH	0.09 pH units	1.1%	0.94
Turbidity	3.2 NTU	12.4%	0.81
Temperature	0.4°C	1.8%	0.96
Dissolved Oxygen	0.3 mg/L	4.7%	0.89

The forecasting model demonstrated excellent performance for pH, temperature, and dissolved oxygen, with R-squared scores above 0.89 indicating that the model explained most of the variance in these parameters. The mean absolute percentage error for pH of 1.1 percent and for temperature of 1.8 percent demonstrates high forecasting accuracy suitable for operational decision-making. Turbidity forecasting proved more challenging, with a mean absolute percentage error of 12.4 percent and an R-squared score of 0.81. Comparison with baseline persistence models, which simply predicted that future values would equal current values, showed that the LSTM model reduced forecast error by 37 percent for turbidity and 42 percent for dissolved oxygen, confirming the effectiveness of the machine learning approach within the simulated environment (Chen et al., 2020)

4.3.2 Anomaly Detection Performance

The Isolation Forest algorithm for anomaly detection was trained on the first two months of simulated data, which was assumed to represent normal simulated operating conditions. The model was configured with one hundred estimators and a contamination parameter of 0.05, meaning it expected approximately five percent of observations to be anomalies. The model's performance was evaluated against a validation dataset of forty-eight simulated water quality samples that had been classified using reference benchmark criteria as either normal or contaminated based on simulated exceedance of Zimbabwean drinking water standards. Table 4.4 presents the anomaly detection performance metrics (Tufail et al., 2023).

Table 4. 4: Anomaly Detection Model Performance

Metric	Value
Precision	0.92
Recall	0.89
F1-Score	0.90
ROC-AUC	0.96
False Positive Rate	3.2%
False Negative Rate	11.0%

The anomaly detection model achieved an F1-score of 0.90, indicating excellent overall performance in identifying water quality anomalies. The precision of 0.92 means that when the model flagged an anomaly, there was a ninety-two percent probability that the water quality was genuinely abnormal, minimising the risk of false alarms that could lead to unnecessary interventions and loss of confidence in the system. The recall of 0.89 indicates that the model successfully detected eighty-nine percent of genuine contamination events, missing eleven percent of events that were later confirmed using reference benchmark evaluation (Muharemi et al. 2019). Review of the missed events revealed that they typically involved subtle deviations in a single parameter just above regulatory thresholds, suggesting opportunities for further model refinement. The ROC-AUC of 0.96 demonstrates excellent discriminative ability, meaning the model effectively distinguishes between normal and anomalous conditions across a wide range of threshold settings.

During simulation period, the anomaly detection system generated twenty-three alerts across all monitoring locations. Of these, twenty-one were confirmed as genuine anomalies through simulated follow-up evaluation, giving a positive predictive value of 91.3 percent. The two false alerts were traced to temporary simulated sensor irregularities, highlighting the highlighting the importance of integrating simulated sensor health monitoring with anomaly detection. The average time from anomaly occurrence to alert generation was 4.3 minutes, well within the requirement for timely simulated operational response.

4.3.3 Comparison with Benchmark Studies

To contextualise the performance of the developed system, its key metrics were compared with recent benchmark studies in IoT-based water quality monitoring. The AquaSurveil multi-agent platform reported in a 2025 study achieved an ROC-AUC of 0.96 for anomaly detection, which matches the performance achieved in this study. A 2025 study on AI-enabled water quality monitoring using LoRaWAN reported sensor accuracies ranging from 94.9 percent to 98.1 percent and an F1-score of 93.1 percent for anomaly detection, which are consistent with the 94.2 to 98.9 percent sensor accuracies and 0.90 F1-score achieved in this research. Another 2025 study evaluating machine learning models for water quality assessment found that AdaBoost achieved a mean absolute error of 14.37 counts per 100 mL for E. coli prediction, demonstrating the viability of machine learning approaches for biological water quality parameters. These comparisons confirm that the simulated system developed for the Bindura community case study achieves performance levels comparable to or exceeding those reported in contemporary international research.

4.4 Discussion of Findings

The results presented in this chapter demonstrate that the developed AI and IoT-based smart water quality monitoring system successfully addresses the challenges identified in Chapter 1. The system achieves reliable, continuous monitoring of critical water quality parameters with accuracy levels suitable for regulatory compliance and simulated operational decision-making. The integration of AI for time-series forecasting and anomaly detection provides enhanced capabilities beyond traditional monitoring approaches, enabling proactive rather than reactive water quality management.

The sensor accuracy results, with all parameters achieving above ninety-four percent agreement with standard reference datasets, confirm that low-cost IoT sensors can provide data of sufficient quality for community water monitoring applications. This finding is particularly significant for resource-constrained environments like Zimbabwe, where expensive laboratory-grade monitoring equipment may be unaffordable or impractical to maintain. The mean absolute error of 0.12 pH units and 0.3°C for temperature meet the accuracy requirements specified in international standards for drinking water monitoring. The communication architecture, combining Wi-Fi with GSM failover, proved effective in addressing the connectivity challenges typical of Zimbabwean urban areas. The overall data transmission success rate of 97.1 percent demonstrates that reliable IoT monitoring is achievable even in infrastructure-constrained environments. The higher latency observed under simulated GSM communication conditions at the Bindura central monitoring scenario , averaging 8.7 seconds, remains acceptable for monitoring applications where real-time response within seconds is not critical. This finding aligns with systematic review findings that LoRa and NB-IoT technologies offer enhanced communication reliability in remote or infrastructure-limited areas.

The AI model performance validates the value of machine learning integration in water quality monitoring systems. The LSTM forecasting model's ability to predict turbidity events up to twelve hours in advance provides actionable lead time for simulated treatment process optimisation. The anomaly detection model's F1-score of 0.90 and ROC-AUC of 0.96 compare favourably with recent research reporting similar metrics for advanced water quality monitoring systems. The false positive rate of 3.2 percent, while low, still generated occasional unnecessary alerts, highlighting opportunities for refinement through integration of additional contextual data such as rainfall measurements and treatment plant operational status.

The user acceptance results confirm that the system meets the practical needs of community water management. The high ratings for clarity of visualisations and usefulness of real-time data indicate that the dashboard design successfully translates complex sensor data into actionable information. The slightly lower confidence in system accuracy, while still positive, suggests the importance of maintaining parallel manual monitoring during initial deployment to build user trust in automated systems. This finding underscores the need for change management and training programmes

when introducing advanced monitoring technologies in organisations accustomed to traditional methods.

4.5 Summary

This chapter has presented the implementation and simulation-based evaluation of the AI and IoT-based smart water quality monitoring system for Bindura. The prototype was evaluated using representative datasets and simulated operating scenarios across four modelled monitoring environments. Results demonstrated strong system performance in terms of data handling, predictive analytics, anomaly detection, and dashboard usability. The findings indicate that the proposed system has potential to provide a reliable and effective solution for improving water quality monitoring in Zimbabwean urban communities, subject to future physical implementation and field validation. The prototype was evaluated within a simulation environment using data generated for four selected monitoring locations over a simulated three-month period, producing over 34,000 virtual water quality readings for analysis. The simulation framework demonstrated stable system operation, with high data processing and transmission reliability throughout the evaluation process.

Validation of the simulated parameter generation process showed that the prototype was able to produce realistic water quality values consistent with expected ranges for all monitored parameters, with pH and temperature simulations showing particularly strong consistency with reference patterns. The AI forecasting model demonstrated strong predictive performance, with R-squared scores of 0.94 for pH, 0.96 for temperature, and 0.89 for dissolved oxygen, while turbidity forecasting achieved an R-squared score of 0.81, demonstrating useful predictive capability for identifying potential contamination trends.The anomaly detection model achieved an F1-score of 0.90 and ROC-AUC of 0.96, indicating strong performance in identifying simulated abnormal water quality events while maintaining a low false positive rate. Prototype usability evaluation also produced positive feedback, with mean satisfaction ratings above 4.4 out of 5 across key usability dimensions, suggesting that the system interface and functionality were acceptable for monitoring and decision-support purposes.These findings demonstrate that the developed prototype provides a reliable and effective simulation-based proof of concept for smart water quality monitoring in Zimbabwean urban communities, with performance metrics comparable to those reported in related international studies.

CHAPTER 5: SUMMARY, CONCLUSIONS AND RECOMMENDATIONS

5.0 Introduction

This chapter highlights the summary of the research carried out, the conclusions drawn from the research findings, recommendations, weaknesses of the research, and possible future research. In this research, an AI and IoT-based Smart Water Quality Monitoring and Early Warning System for water resources within communities in Zimbabwe was designed and simulated. Data collected through simulation from selected boreholes and wells in Bindura town was utilized to analyze and evaluate the proposed system. This research sought to overcome the problems of existing water quality monitoring methods, which are manual, labor-intensive, and lack the capability to offer real-time information. These challenges were tackled in this research through the integration of simulated IoT sensing techniques with artificial intelligence approaches (Salih et al. 2019)

5.1 Summary of the Study

This research was initiated owing to the growing difficulties involved in water quality monitoring in Zimbabwean settlements. The process involved in monitoring the water quality manually was noted as being time-consuming, laborious, and could not provide continuous water quality monitoring. These weaknesses contribute to delayed detection of contamination and increased exposure of communities to unsafe water conditions and water-borne diseases.

In summary, this research proposed the design of an intelligent monitoring system that can monitor the various water quality parameters like pH, turbidity, temperature, dissolved oxygen, and total dissolved solids through IoT sensors that will be connected to microcontroller devices like ESP32 or Arduino (Shumba et al. 2022).This system will transfer the sensed information to a cloud platform where Artificial Intelligence will analyze the data for any abnormality and predict any potential contamination threats.

The specific objectives of the study were to:

1. To analyse the different techniques that can be used for water quality monitoring.

2. To design an IoT based system for water quality testing and monitoring.
3. Evaluate the effectiveness of the proposed system.

The study established that the integration of AI and IoT technologies significantly improves water quality monitoring through:

- Continuous real-time monitoring,
- Automated data collection,
- Faster contamination detection,
- Predictive analysis capabilities,
- Remote accessibility,
- and automated alert generation.

The developed prototype demonstrated the ability to monitor selected water quality parameters continuously and transmit data for analysis and visualization. The AI component was able to identify abnormal trends and generate predictive insights regarding possible contamination risks. The system therefore demonstrated potential to improve community-level water quality management and support proactive intervention strategies.

5.2 Conclusions

The study concludes that traditional water quality monitoring approaches used in many communities are inadequate for addressing modern water management challenges because they rely heavily on manual sampling and delayed laboratory analysis. These approaches limit the ability of communities and responsible authorities to detect contamination early and respond promptly to water quality threats (WHO, 2022).

Moreover, it can be stated that using IoT and Artificial Intelligence technology is an efficient method to optimize the water quality monitoring system. In particular, IoT sensors help monitor different parameters related to water, while AI helps enhance analysis through anomaly detection and prediction (Zulkifli et al. 2022)

The developed AI and IoT-Based Smart Water Quality Monitoring and Early Warning System has proven the feasibility of smart technology utilization in community water source monitoring. This was done via increasing efficiency in data collection, improving the visibility of water quality, and enabling early warnings of unsafe water.

Another important conclusion that can be drawn from the findings of the research is the higher degree of feasibility of decentralized systems of water source monitoring rather than those that are central. This is due to the fact that water contamination may happen in various stages, including water sources, water storage facilities, water transmission routes, and household practices.

In general, the study showed the huge potential of AI and IoT technologies in terms of monitoring water quality.

5.3 Recommendations

Based on the findings and conclusions of the study, the following recommendations are proposed:

5.3.1 Adoption of Smart Water Monitoring Technologies

Communities, local authorities, and environmental agencies should adopt IoT and AI-based monitoring systems to improve real-time monitoring of community water sources and strengthen early contamination detection mechanisms.

5.3.2 Expansion of Monitoring Infrastructure

Future implementations should expand the monitoring system to cover multiple boreholes, wells, communal taps, and storage facilities across different communities to improve coverage and data availability.

5.3.3 Integration with Mobile and Web Applications

The developed system should be integrated with mobile applications and web dashboards that allow community members, health authorities, and environmental officers to access real-time water quality information remotely.

5.3.4 Community Awareness and Training

Communities should be educated on the importance of water quality monitoring and trained on how to interpret alerts and respond appropriately whenever contamination risks are detected.

5.3.5 Government and Stakeholder Support

Government institutions, municipalities, non-governmental organizations, and development partners should provide financial and technical support towards the implementation of smart water monitoring technologies in vulnerable communities.

5.3.6 Integration of Advanced AI Models

Future systems should incorporate more advanced machine learning and predictive analytics models capable of improving contamination prediction accuracy and supporting intelligent decision-making.

5.4 Limitations of the Study

The study faced several limitations.

Firstly, the research focused mainly on simulated prototype development and evaluation rather than full-scale deployment due to limited financial and technical resources.

Secondly, the study monitored selected water quality parameters only, which may not fully represent all possible forms of water contamination.

Additionally, since the research mainly relied on simulations and prototype tests, variables like environmental changes, need for calibration of sensors, possibility of failure in hardware and network connections have not been taken into account. This can affect the data gathering process once it goes into the practical realm.

Finally, the project evaluation was mainly through simulation and prototype testing as opposed to real application in actual community water sources. Therefore, the results obtained might not reflect all possible scenarios encountered in various parts of Zimbabwe. This means that the performance of the proposed method would be impacted by the varied settings.

5.5 Areas for Future Research

Future studies may focus on:

- Large-scale deployment of smart water monitoring systems across rural and urban communities.
- Integration of additional sensors for detecting chemical and biological contaminants.
- Development of solar-powered and energy-efficient monitoring systems.
- Integration of Geographic Information Systems (GIS) for spatial visualization of contamination risks.
- Use of deep learning models for more advanced predictive analysis.
- Integration of SMS and mobile notification systems for community-based early warning communication.

5.6 Chapter Summary

This chapter presented the summary, conclusions, recommendations, limitations, and future research directions for the study. The study concluded that AI and IoT technologies provide an effective and practical solution for improving community water quality monitoring through real-time data collection, predictive analysis, and early warning capabilities. The developed system demonstrated the potential to improve public health protection, support proactive water management, and enhance access to safe water within communities in Zimbabwe.

References

1. Liao, Y., Yu, G., Yuan, C., Srivastava, G., & Lin, J. C.-W. (2023). *A survey of Internet of Things and cyber-physical systems: Standards, algorithms, applications, security, challenges, and future directions*. *Information, 14*(7), 388.
2. Chen, Y., Han, D. and Yan, X., 2020. Water quality prediction using machine learning methods. *Water*, 12(5), pp.1-15.
3. Tufail, S., Riggs, H., Tariq, M., & Sarwat, A. I. (2023). *Advancements and challenges in machine learning: A comprehensive review of models, libraries, applications, and algorithms*. *Electronics, 12*(8), 1789.
4. Ouma, Y., Opudo, J. and Nyambenya, T., 2018. Smart water management using Internet of Things technologies. *Journal of Environmental Monitoring*, 20(4), pp.200–210.
5. Salih, N.A.J., Hasan, I.J. and Abdulkhaleq, N.I., 2019. Design and implementation of a smart monitoring system for water quality. *Indonesian Journal of Electrical Engineering and Computer Science*, 14(1), pp.44-50.
6. Shumba, E., Moyo, N., Ndlovu, B. and Nleya, S., 2022. IoT adoption readiness in water and sanitation management in Zimbabwe. *Zimbabwe ICT Conference Proceedings.*
7. Zulkifli, C.Z., Yusof, R., Abdullah, M. and Hashim, H., 2022. IoT-based water monitoring systems: A systematic review. *Water*, 14(22), pp.1-23.
8. Salih, N.A.J., Hasan, I.J. and Abdulkhaleq, N.I., 2019. Design and implementation of a smart monitoring system for water quality. *Indonesian Journal of Electrical Engineering and Computer Science*, 14(1), pp.44-50.
9. Shumba, E., Moyo, N., Ndlovu, B. and Nleya, S., 2022. An assessment of Internet of Things (IoT) adoption readiness in water and sanitation in Zimbabwe: A case of the City of Gweru. *Zimbabwe Conference of Information and Communication Technologies*.
10. Zulkifli, C.Z. et al., 2022. IoT-based water monitoring systems: A systematic review. *Water*, 14(22), pp.1-23.
11. Salih, N.A.J., Hasan, I.J. and Abdulkhaleq, N.I., 2019. Smart monitoring system for water quality using IoT technologies. *Indonesian Journal of Electrical Engineering and Computer Science.*
12. World Health Organization. (2022).Guidelines for drinking-water quality (4th ed.).WHO Press.

13. Kim, S., Park, S., & No, K. (2019).A survey on IoT-based water quality monitoring sytems._Sensors, 19_(12),2881.
14. Diamantini, C.,Potena, D., &Storti, E. (2018). KDD techniques for smart water quality monitoring: A review._Journal of Big Data, 5_(1),1-19.
15. Adedoja, O.S.,Hamam,Y., Khalaf,B.,& Sadiku, F.(2020). Smart water quality monitoring systems in Africa: A review._Sensors, 20_(21), 6180.
16. World Health Organization.(2017). Water quality and health review. WHO Press.
17. Siwo,G.H,Nyaga, J.,& Makokha, G. (2021). Design and evaluation of an IoT-based water quality monitoring system for rural Kenya._African journal of Science, Technology, Innovation and Development, 13_(4), 401-412.
18. Geeks for Geeks. (2023). IoT based water quality monitoring system using Arduino.Retrieved from geeksforgeeks.org
19. Vijayaraghavan,V., Gopinath,P.,& Ravindran, G. (2021). Predictive analytics for water quality monitoring using LSTM networks._Environmental monitoring and Assessment, 193_(7), 1-15.
20. Creswell, J. W., & Creswell, J.D. (2018). Research design: Qualitative, quantitative, and mixed methods approaches (5th ed.). SAGE Publications.
21. Machete, F., & Marques, R.C (2021).Challenges of water service provision in Sub-Saharan Africa. Utilities Policy, 70,101202.
22. Dalu, T., et al. (2017).Water quality and human health risks in rural drinking water sources in Zimbabwe. Environmental Monitoring and Assessment, 189, 550.
23. UNICEF & WHO. (2022).Progress on household drinking water, sanitation and hygiene 2000-2020. Joint Monitoring Programme.
24. Aldosari, A., et al.(2020). Real-time dashboard for IoT-based environmental monitoring. 2020 7th International Conference on Computing for Sustainable Global Development.
25. Maier, A., et al. (2017).The Internet of Things for water sustainability. 2017 IEEE Confernce on Technologies for Sustainability.
26. Musika, A. (2024). Assessing physic-chemical and microbiological groundwater quality of Kitsiyatota catchment area in Bindura,Zimbabwe[*Bachelor's dissertation, Bindura University of Science Education]*.

27. Gwature, J. (2024). Unregulated mining has compromised Bindura water quality and quantity- Bindura mayor. NewsDay.
28. Bindura University of Science Education. (2024). Cholera index case linked to contaminated boreholes/wells in Pfupajena, Bindura. BUSE Dissertation.
29. Botta, A., et al. (2016).Integration of cloud computing and Internet of Things: A survey. Future Generation Computer Systems, 56, 684-700.
30. Espressif Systems. (2023). ESP32 Technical Reference Manual. Espressif Inc.
31. Muharemi,F., et al. (2019). Water contamination monitoring with anomaly detection using IoT time-series data.2019 *IEEE 5th World Forum on Internet of Things.*
32. Mckinney, W. (2017). Python for Data Analysis. *O'Reilly Media*.
33. Ahmed, U., et al. (2019). Machine learning for drinking –water quality classification: Towards efficient water quality monitorin. *2019 IEEE 5th International Conference on Smart Instrumentation.*
34. Kamyab, H., et al. (2023). Al –driven real-time water quality prediction using IoT sensors.*Journal of Environmental Management, 325, 116627*.
35. Haghiabi,A. H., et al. (2018). Water quality prediction using machine learning methods. *Water quality research journal, 53910(1), 3-13*.
36. Alaka, S.A. (2025).Integrating Machine Learning Learning and IoT Technologies for Smart Water Quality Monitoring:Methods,Challenges, and Future Directions._*International Journal of Data Science and Big Data Analytics,5_(2) 46-68.*
37. Cordor, R. M., Jr. (2025). Design and implementation of an automated zebrafish feeding and water quality monitoring system with spectrophotometric analysis [*Master's thesis, University of Maryland Eastern Shore]*.
38. Hellos.Blog. (2024, June). Strategic insights into semiconductor plating system growth. *Hellos.blog*
39. Gong, J., Guo, X., & Hu, C. (2023). Review of urban drinking water contamination source identification methods. *Energies,_16_(2), 705. Doi.org*
40. Agone,V.M., Muthurajan, S., Prabhakaran, G., & Chavan, C.S (2026). Artificial intelligence and IoT for disaster risk management and sustainable environmental sytems(1st ed.).RAD Emics.

41. Rekha, K.R., Impana, R., Hamsa, J., Divya, K., & Harshitha, R.S. (2025). IoT-Based Real Time Water Quality Detection System. International Journal of Advanced Research in Computer and Computation Engineering, *14(12),Article 1017148/IJARCCE.2025.141277.doi.org*

42. Peffers, K., Tuunanen, T., Rothenberger, M. A., & Chatterjee, S. (2007). A design science research methodology for information systems research. *Journal of Management Information Systems, 24(3), 45–77.*